

Cyphertag® Tags |



Our high-performance, durable RFID tag products have a proven track record in a variety of applications including hands-free access control, time and attendance, emergency evacuation monitoring, including ATEX versions available for hazardous environments.



TV4 | Key-fob

Robust Key-fob suitable for key tagging applications.

Features

- ✓ Hands-free reading range (>2.0m)
- ✓ Touch free Access Control
- ✓ Inert until in reader detection zones
- ✓ High fidelity reading (1:100 million error rate)
- ✓ Battery low indicator via the reader
- ✓ Stainless steel attachment point
- ✓ Robust design for harsh environments
- ✓ Key tagging
- ✓ Personnel Identification

Technical Specification

Specification	Details
Physical Size	55 x 42 x 11.5mm
Temperature Range	-20°C to +60°C (-4°F to 140°F)
Humidity	100% condensing
Battery Life	Typically >5 years based on 6 minutes per day
Battery Low	Provides 2-3 months notice of demise based on 6 minutes daily use
Read Range	Determined by reader and aerial size, up to 2m (6.5 ft)
Speed of Reading	Typically 20 per second
Approvals	CE, UKCA, ETSI



UK MANUFACTURER

Identec Ltd 5 Mercantile Rd
Houghton le Spring DH4 5PH



+44 (0)191 584 4084



info@identec.com



identeclimited
Web www.identec.com

With nearly 40 years of experience in touch-free radio frequency identification systems, our technology products are used around the globe, providing innovative solutions for a wide range of application and industries. Check out our full product range at www.identec.com or to discuss your bespoke requirements regarding our RFID products please [get in touch](#).