

# Cyphertag® Tags |



Our high-performance, durable RFID tag products have a proven track record in a variety of applications including hands-free access control, time and attendance, emergency evacuation monitoring, including ATEX versions available for hazardous environments.



## TV6 | Photo ID Tag

Photo ID tag suitable for applications where the users ID must be visible at all times. The TV6 tag is designed to co-exist with existing 13.56MHz passive cards.

### Features

- ✓ Hands-free reading range (>3.0m)
- ✓ Touch-Free Access Control
- ✓ Inert until in reader detection zones
- ✓ High fidelity reading (1:100 million error rate)
- ✓ Replaceable battery
- ✓ ISO Photo ID card compatible
- ✓ Mass Evacuation
- ✓ Personnel Safety
- ✓ Personnel Identification

### Technical Specification

Specification	Details
Physical Size	95 x 64 x 5mm
Temperature Range	-20°C to +60°C (-4°F to 140°F)
Humidity	0 - 80% non condensing
Battery Type	Replaceable Lithium CR2025
Battery Life	Typically >2.5 years based on 6 minutes per day
Battery Low	Typically 1-2 months notice of demise based on 6 minutes daily use
Read Range	Determined by reader and aerial size, up to 3m (9.5 ft)
Speed of Reading	Typically 20 per second
Approvals	CE, UKCA, ETSI



UK MANUFACTURER

Identec Ltd 5 Mercantile Rd  
Houghton le Spring DH4 5PH

+44 (0)191 584 4084  
info@identec.com

identeclimited  
Web www.identec.com

With nearly 40 years of experience in touch-free radio frequency identification systems, our technology products are used around the globe, providing innovative solutions for a wide range of application and industries. Check out our full product range at [www.identec.com](http://www.identec.com) or to discuss your bespoke requirements regarding our RFID products please [get in touch](#).