Cyphertag® Tags |

Our high-performance, durable RFID tag products have a proven track record in a variety of applications including hands-free access control, time and attendance, emergency evacuation monitoring, including ATEX versions available for hazardous environments.

Features

✓ Hands-free reading range (>2.0m)

✓ Touch-Free Access Control

✓ Inert until in reader detection zones

✓ High fidelity reading
(1:100 million error rate)

✓ Robust design

✓ Battery low indicator via the reader

✓ Article Identification

✓ Car Parking Access

TV3 | Metallic Article Tag

Article tag suitable for applications where a metallic item requires tagging.

Technical Specification

Specification	Details
Physical Size	76 x 56 x 7mm
Temperature Range	-20°C to +60°C (-4°F to 140°F)
Humidity	100% condensing
Mounting	Metallic
Battery Life	Typically >5 years based on 6 minutes per day
Battery Low	Provides 2-3 months notice of demise based on 6 minutes daily use
Read Range	Determined by reader and aerial size, up to 2m (6.5 ft)
Speed of Reading	Typically 20 per second
Approvals	CE, UKCA, ETSI

UK MANUFACTURER

With nearly 40 years of experience in touch-free radio frequency identification systems, our technology products are used around the globe, providing innovative solutions for a wide range of application and industries. Check out our full product range at www.identec.com or to discuss your bespoke requirements regarding our RFID products please get in touch.